0110101 5-29-03

Atty. Dkt.: 073169-0261847

IN THE CLAIMS

1. (Currently Amended) A communications and data display system comprising:

a projection system including a projector high speed radio frequency (RF) wireless transceiver and a controller; and

a first data appliance including a first-high-speed RF wireless transceiver, wherein:

the first-high-speed RF wireless transceiver transfers graphical data to the projector-high-speed RF wireless transceiver;

the projection system displays the graphical data; and

the transfer and the display of the graphical data is controlled by the controller using first control data.

2. (Currently Amended) The communications and data display system of claim 1, further comprising:

a second data appliance including a second-high-speed RF wireless transceiver, wherein:

the first high-speed RF wireless transceiver transfers a first signal to the projector high-speed RF wireless transceiver;

the projector-high speed RF wireless transceiver transfers the first signal to the second-high-speed RF wireless transceiver; and

the transfer of the first signal from the first data appliance to the second data appliance is controlled by the controller using second control data.

3. (Currently Amended) The communications and data display system of claim 2, wherein:

the second-high-speed-RF wireless transceiver transfers a second signal to the projector high-speed RF wireless transceiver;

the projector-high-speed RF wireless transceiver transfers the second signal to the first

high-speed RF wireless transceiver; and

0

180 + 18

the transfer of the second signal from the second data appliance to the first data appliance is controlled by the controller using the second control data.

4. (Currently Amended) The communications and data display system of claim 1, wherein:

the projection system further comprises an interface to an external network;

the first-high speed RF wireless transceiver transfers a first signal to the projector-highspeed RF wireless transceiver;

the projector-high-speed-RF wireless transceiver transfers the first signal to the external network and

the transfer of the first signal from the first data appliance to the external network is controlled by the controller using third control data.

5. (Currently Amended) The communications and data display system of claim 4, wherein:

the external network transfers a second signal to the projector-high-speed RF wireless transceiver;

the projector high-speed RF wireless transceiver transfers the second signal to the first high-speed RF wireless transceiver; and

the transfer of the second signal from the external network to the first data appliance is controlled by the controller using the third control data.

6. (Currently Amended) The communications and data display system of claim 1, wherein:

the first data appliance further comprises a graphics chip, a processing unit, a memory and a MUX;

the processing unit takes keyboard input from a local keyboard;

the processing unit takes memory graphics input from the memory and provides processing-unit memory output to the memory;

the processing unit provides processing-unit graphics output to the graphics chip and to the MUX;

the processing unit provides processing-unit control output to the MUX; the graphics chip provides graphics-chip output to a local display and to the MUX; and the MUX provides MUX output to the first-high-speed RF wireless transceiver, the MUX output having a compression format selected from the group consisting of compressed and uncompressed.

7. (Currently Amended) The communications and data display system of claim 1, wherein:

the projection system further comprises a graphics converter and a projector;
the graphics converter receives the graphical data from the projector-high-speed RF
wireless transceiver and transfers uncompressed graphical data to the projector;
and

the projector displays the uncompressed graphical data.

- 8. (Previously Amended) The communications and data display system of claim 7, wherein the graphics converter includes an application-aware graphics chip that transforms compressed graphics data to the uncompressed graphics data.
- 9. (Previously Amended) The communications and data display system of claim 8, wherein: the compressed graphical data includes compressed motion graphics or video data; and the uncompressed graphical data includes uncompressed motion graphics or video data.
- 10. (Currently Amended) A communications and data display system comprising:
 a projection system including a projector-high-speed radio frequency (RF) wireless
 receiver and a controller; and

a first data appliance including a first-high-speed RF wireless transmitter, wherein:

the first <u>high-speed RF wireless</u> transmitter transfers graphical data to the projector-<u>high-speed RF wireless</u> receiver;

the projection system displays the graphical data; and
the transfer and the display of the graphical data is controlled by the controller
using control data.

11. (Currently Amended) The communications and data display system of claim 10, wherein:

the first data appliance further comprises a graphics chip, a processing unit, a memory and a MUX;

the processing unit takes keyboard input from a local keyboard;

the processing unit takes memory graphics input from the memory and provides processing-unit memory output to the memory;

the processing unit provides processing-unit graphics output to the graphics chip and the MUX;

the processing unit provides processing-unit control output to the MUX; the graphics chip provides graphics-chip output to a local display and to the MUX; and the MUX provides MUX output to the first-high-speed RF wireless transmitter, the MUX output having a compression format selected from the group consisting of compressed and uncompressed.

12. (Currently Amended) The communications and data display system of claim 10, wherein:

the projection system further comprises a graphics converter and a projector;
the graphics converter receives the graphical data from the projector high-speed RF
wireless receiver and transfers uncompressed graphical data to the projector; and
the projector displays the uncompressed graphical data.

- 13. (Previously Amended) The communications and data display system of claim 12, wherein the graphics converter includes an application-aware graphics chip that transforms compressed graphics data to the uncompressed graphics data.
- 14. (Currently Amended) A method for communication and data display, comprising:
 transmitting graphical data from a first-high-speed radio frequency (RF) wireless
 transceiver of a first data appliance to a projector-high-speed RF wireless
 transceiver of a projection system;

displaying the graphical data with the projection system; and

controlling the transmitting of the graphical data and the displaying of the graphical data with a controller using first control data.

(N) 15.

PA

(Currently Amended) The method of claim 14, further comprising:

transmitting a first signal from the first-high speed RF wireless transceiver to the projector-high-speed RF wireless transceiver;

transmitting the first signal from the projector-high-speed RF wireless transceiver to a second high-speed RF wireless transceiver of a second data appliance; and controlling the transmission of the first signal from the first data appliance to the second

data appliance with the controller using second control data.

16. (Currently Amended) The method of claim 15, further comprising:

transmitting a second signal from the second high speed RF wireless transceiver to the projector high speed RF wireless transceiver;

transmitting the second signal from the projector high-speed RF wireless transceiver to the second high speed RF wireless transceiver; and

controlling the transmission of the second signal from the second data appliance to the first data appliance with the controller using the second control data.

17. (Currently Amended) The method of claim 14, further comprising:

transmitting a first signal from the first high-speed RF wireless transceiver to the projector high-speed RF wireless transceiver;

transmitting the first signal from the projector-high-speed RF wireless transceiver to an external network, the projection system including an interface to the external network; and

controlling the transmission of the first signal from the first data appliance to the external network with the controller using third control data.

18. (Currently Amended) The method of claim 17, further comprising:
transmitting a second signal from the external network to the projector-high-speed RF
wireless transceiver;

O

ont

transmitting the second signal from the projector-high-speed RF wireless transceiver to the first-high-speed RF wireless transceiver; and

controlling the transmission of the second signal from the external network to the first data appliance with the controller using the third control data.

19. (Currently Amended) The method of claim 14, further comprising: transmitting a keyboard input from a local keyboard to the first data appliance; converting compressed graphical data to uncompressed graphical data at the first data appliance; and

controlling a flow of uncompressed graphical data and compressed graphical data to the first-high-speed RF wireless transceiver.

- 20 (Previously Amended) The method of claim 19, wherein: the compressed graphical data includes compressed motion graphics or video data; and the uncompressed graphical data includes uncompressed motion graphics or video data.
- 21. (Original) The method of claim 14, further comprising: converting compressed graphical data to uncompressed graphical data at the projection system; controlling a flow of uncompressed graphical data to a projector of the projection system; and using the projector to display uncompressed graphical data.
- 22. (Original) The method of claim 21, wherein converting compressed graphical data to uncompressed graphical data includes using an application-aware graphics chip to transform compressed graphical data to uncompressed graphical data.
- (Currently Amended) The communications and data display system of claim 1, wherein the first control data includes at least one of:

 projector control data of the projection system; and

09/492,728 to Naden

7

CH

a first control signal of the first data appliance transferred from the first high speed RF wireless transceiver to the controller via the projector high speed RF wireless transceiver.

24. (Currently Amended) The communications and data display system of claim 2, wherein the second control data includes at least one of:

projector control data of the projection system;

- a first control signal of the first data appliance transferred from the first-high-speed RF wireless transceiver to the controller via the projector-high-speed RF wireless transceiver; and
- a second control signal of the second data appliance transferred from the second highspeed RF wireless transceiver to the controller via the projector high-speed RF wireless transceiver.
- 25. (Currently Amended) The communications and data display system of claim 4, wherein the third control data includes at least one of:

projector control data of the projection system;

a first control signal of the first data appliance transferred from the first high-speed RF wireless transceiver to the controller via the projector-high-speed RF wireless transceiver; and

an external control signal of the external network transferred to the controller via the interface to the external network.

26. (Currently Amended) The communications and data display system of claim 10, wherein the control data includes at least one of:

projector control data of the projection system; and

a first control signal of the first data appliance transferred from the first high-speed RF wireless transmitter to the controller via the projector high-speed RF wireless receiver.

"IONT

(Currently Amended) The communications and data display system of claim 14, wherein the first control data includes at least one of:

projector control data of the projection system; and

a first control signal of the first data appliance transferred from the first-high-speed-RF

wireless transceiver to the controller via the projector-high-speed RF wireless

transceiver.

28. (Currently Amended) The communications and data display system of claim 15, wherein the second control data includes at least one of:

projector control data of the projection system;

- a first control signal of the first data appliance transferred from the first-high-speed RF

 wireless transceiver to the controller via the projector-high-speed RF wireless

 transceiver; and
- a second control signal of the second data appliance transferred from the second-highspeed RF wireless transceiver to the controller via the projector-high-speed RF wireless transceiver.
- 29. (Currently Amended) The communications and data display system of claim 17, wherein the third control data includes at least one of:

projector control data of the projection system;

a first control signal of the first data appliance transferred from the first high-speed RF

wireless transceiver to the controller via the projector-high-speed RF wireless

transceiver; and

an external control signal of the external network transferred to the controller via the interface to the external network.